

MÁRIO JOSÉ WERNER & CIA LTDA WERNER MADEIRAS

Werner Madeiras is a timber industry that has been in the market since 1986 and has been growing rapidly in the Pine market.

Werner Madeiras is known widely not only for delivering a high quality product, but also for providing superior service to its customers and for honoring its contracts. We can ensure stable and uniform dimensions of sawn and surfaced wood, all Kiln Dried at 12% (+/-2%).



PINE LUMBER

Cut Lumber from Pinus (without pitch or knots)

This wood is extracted only from the log core, free of pitches or knots and of high density. The wood is dried and heat treated to an 8-12% moisture level, an ideal condition for the lumber and the processes it will go through before the final output.

Cut Lumber from Pinus (with pitch or knots)

We have a product with presence of pitches, however it is still quality lumber. Since the lumber is cut from the entire log especially from its core, some pieces have knots and pitches.

SPECIFICATIONS

Species: *Pinus taeda* and *Pinus elliottii*

Average Density (MC 12%): +/- 490 kg/m³

Kiln Dried: 12% (+/-2%).

USES AND APPLICATIONS

Due to its versatility, cutting precision and high quality finish, it can be used in various stages of construction, for producing furniture and components, pallets and other packaging, etc.

AVAILABLE SIZES (MM):

Thickness: 20 / 22 / 25 / 28 / 32 / 38 / 45 / 50 / 65 / 75 / 90 / 95 / 100

Width: 75 / 95 / 100 / 125 / 150 / 175 / 200 / 225 / 250 / 300

Length: 1000 / 1500 / 3000

* OTHER DIMENSIONS UPON REQUEST.

* IT'S POSSIBLE TO PRODUCE S4S.



EUCALYPTUS LUMBER

Cut Lumber from Eucalyptus (with knots)

This wood come from forests of *Eucalyptus gradis* whith Average Density 700 kg/m³. The wood is dried and heat treated to an 12% moisture level, an ideal condition for the lumber and the processes it will go through before the final output.

USES AND APPLICATIONS

- Construction
- Furniture

AVAILABLE SIZES (MM):

Thickness: 25 / 30 / 40

Width: 75 / 95 / 100 / 125 / 150/ 175 / 200

Length: 1000/ 1500/ 3000

Cut Lumber from Eucalyptus (with pitch or knots)

This wood come from forests of *Eucalyptus gradis* whith Average Density 620 kg/m³. The wood is dried on the air dried system to an 20% moisture level, an ideal condition for the packagings.

USES AND APPLICATIONS

- Packaging

AVAILABLE SIZES (MM):

Thickness: 20/ 25

Width: 70 / 100 / 125 / 150

Length: 1000 / 1200 / 1500 / 2400 / 3000

